

Product Code:

**7715**

# O.E.M. LONGLIFE 504 / 507

Fully synthetic engine oil

Meets the requirements:

SAE 5W-30, API SN, ACEA C3-16  
BMW LL-04, MB 229.51, PORSCHE C30  
VW 504.00/507.00/502.00/505.00/503.01/506.00  
VW 505.01/506.01

Synthetic engine oil of the new generation, specially developed for use in all petrol and diesel engines. The high-tech additive package (low SAPS – low content of sulphur, ash and phosphorus) ensures optimal operation of the environmental protection systems as well as of diesel particulate filters (DPF). Effectively protects from wear and ensures exceptional cleanliness of the engine separate parts. Recommended for all modern petrol and diesel engines, among these such meeting the environmental standards Euro 4 und Euro 5. It is used in engines with extended oil change intervals (up to 30,000 km) and without.

Product Characteristics:

Test	Method	Unit	Result
SAE-class			5W-30
Density at 15°C	D 1298	kg/m³	850
Viscosity at 40°C	D 445	CSt	74,53
Viscosity at 100°C	D 445	CSt	11,40
Viscosity at -30°C	D 5293	CP	5563
Viscosity index	D 2270		163
Flash point COC	D 92	°C	224
Pour point	D 97	°C	-42
TBN	D 2896	gKOH/kg	7,58

Volume:

1L	MN7715-1	10L	MN7715-10
1L met.	MN7715-1ME	20L	MN7715-20
5L	MN7715-5	60L	MN7715-60
5L met.	MN7715-5ME	208L	MN7715-DR
		1000L	MN7715-IBC



[www.mannol.de](http://www.mannol.de)

SCT-Vertriebs GmbH  
Feldstrasse 154, 22880 Wedel/Hamburg, Germany, info@sct-germany.de, tel.: +49 (0)4103 1211 0, fax: +49 (0)4103 1211 116

**MANNOL®**