

<b>SICHERHEITSDATENBLATT</b>	Blatt 1/5
 	Druckdatum 03.06.2007
	Überarbeitet am 16.05.2007

Section 1. Chemical Product and Company Identification	
<b>Common name</b>	Beit Tesioner
<b>Supplier</b>	SCT VERTRIEBS GMBH, FELDSTRASSE 154, 22880 WEDEL, GERMANY Tel. +49 (0) 4103 121 10, Fax. +49 (0) 4103 12 11 116 E-mail: info@sct-germany.de Web site: <a href="http://www.sct-germany.de">www.sct-germany.de</a>
<b>Material Uses</b>	Beit Tesioner , Conditioner and Cleaner
<b>Print date</b>	6/2007
<b>In case of emergency</b>	Tel. +49 (0) 4103 121 10

Section 2. Composition And Information On Ingredients				
Name	CAS#	% by Weight	Exposure Limits	
			OSHA	ACGIH
LIQUEFIED PETROLEUM GAS	68475-59-2	30-50	Not available	
HEXANE	110-54-3	30-50	500 ppm	
Mineral oil	68475-59-2	1-5	Not available	
Silicone propyl siloxane	63148-62-9	1-5	Not available	

Section 3. Hazards Identification	
<b>Physical State and Appearance</b>	Aerosol
<b>Emergency Overview</b>	DANGER! FLAMMABLE LIQUID AND VAPOR, VAPOR MAY CAUSE FLASH FIRE, HARMFUL IF SWALLOWED OR INHALED. May cause skin, eye and respiratory irritation. Use only with adequate ventilation.
<b>Routes of Entry</b>	Absorbed through skin. Skin contact. Eye contact. Inhalation.
<b>Potential Acute Health Effects</b>	
<i>Eyes</i>	This product is an eye irritant
<i>Skin</i>	Prolonged skin contact may cause dermatitis with drying and cracking of skin. Permeator (absorbed through the intact skin).
<i>Inhalation</i>	May cause respiratory tract irritation. Inhalation of the vapors may cause dizziness, nausea, headache, or anaesthetic effects.
<i>Ingestion</i>	Not an expected route of entry. Ingestion may cause nausea, vomiting, dizziness, gastrointestinal irritation.
<b>Medical conditions aggravated by overexposure:</b>	Individuals with preexisting lung disease, asthma, or breathing difficulties may have increased susceptibility to the toxicity of excessive exposures.
<b>Overexposure/signs/symptoms</b>	Skin inflammation is characterized by itching, scaling, reddening.

<b>SICHERHEITSDATENBLATT</b>	Blatt 2/5
 	Druckdatum 03.06.2007
	Überarbeitet am 16.05.2007

	Inflammation of the eye is characterized by redness, watering, and itching.
--	---

<b>Section 3. Hazards Identification - cont.</b>	
<b>Risk - phrase(s)</b>	R11: Highly flammable R38: Irritating to skin. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67: Vapours may cause drowsiness and dizziness.
<b>Safety-phrase(s)</b>	S2: Keep out of the reach of children. S16: Keep away from sources of ignition-No smoking. S23: Do not breathe spray. S35: This material and its container must be disposed of in a safe away. S51: Use only in well-ventilated areas.

<b>Section 4. First Aid Measures</b>	
<b>Eye contact</b>	Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
<b>Skin contact</b>	Wash contaminated skin with soap and water. Wash contaminated clothing before reusing. If irritation occurs, seek medical attention.
<b>Inhalation</b>	Allow the victim to rest in a well-ventilated area. Oxygen may be administered if breathing is difficult. If irritation or difficult breathing persists, seek immediate medical attention.
<b>Ingestion</b>	Not an expected route of entry. Do not induce vomiting. Seek immediate medical attention.
<b>Notes to physician</b>	

<b>Section 5. Fire Fighting Measures</b>	
<b>Flammability of the product</b>	Flammable
<b>Flammable limits</b>	
<b>Fire hazards in presence of various substances</b>	Flammable in presence of open flames and sparks. Flammable in presence of heat, of oxidizing materials, of combustible materials. Slightly flammable to flammable in presence of reducing materials.
<b>Fire fighting media and instruction</b>	Flammable liquid, insoluble in water. SMALL SPILL: use DRY chemicals, CO <sub>2</sub> , alcohol foam or water spray. LARGE SPILL: use DRY chemicals, CO <sub>2</sub> , water spray or

<b>SICHERHEITSDATENBLATT</b>	Blatt 3/5
 	Druckdatum 03.06.2007
	Überarbeitet am 16.05.2007

	foam. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
<b>Protective clothing (fire)</b>	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
<b>Special remarks on fire hazards</b>	Container explosion may occur under fire conditions or when heated. Vapor may travel considerable distance to source of ignition and flash back.
<b>Special remarks on explosion hazards</b>	Container explosion may occur under fir conditions or when heated.
<b>Flash point</b>	Not available
<b>Extinguishing media</b>	Foam, carbon dioxide or dry agent
<b>Fire-fighting procedures</b>	Keep container(s) exposed to fire cool, by spraying with water
<b>Unusual exposure hazard</b>	Aerosols may explode if heated above 50°C.
<b>Section 6. Accidental Release Measures</b>	
<b>Small spill and leak</b>	Not applicable due to size and type of container.
<b>Large spill and leak</b>	Not likely due to size of container.

<b>Section 7. Handling and Storage</b>	
<b>Handling</b>	After handling, always wash hands thoroughly with soap and water. Avoid breathing vapors or spray mists. Avoid contact with skin and eyes. Use only with adequate ventilation. Store and use away from heat. Sparks, open flame, or any other ignition source. Keep out of the reach of children. Do not puncture or incinerate container.
<b>Storage</b>	Flammable materials should be stored in a separate safety storage cabinet or room. Keep in a cool, well-ventilated place. Do not puncture, incinerate, store the container at temperatures above 49°C (120°F) or in direct sunlight. Do not freeze.

<b>Section 8. Exposure Controls / Personal Protection</b>	
<b>Engineering controls</b>	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.
<b>Personal protection</b>	
<b>Eyes</b>	No special precautions are necessary if used as intended.
<b>Body</b>	No special precautions are necessary if used as intended.
<b>Respiratory</b>	No special precautions are necessary if used as intended.
<b>Hands</b>	No special precautions are necessary if used as intended.
<b>Feet</b>	No special precautions are necessary if used as intended.

<b>Section 9. Physical and Chemical Properties</b>
--

<b>SICHERHEITSDATENBLATT</b>	Blatt 4/5
 	Druckdatum 03.06.2007
	Überarbeitet am 16.05.2007

<b>Appearance:</b>	
<i>Physical state</i>	Aerosol
<i>Colour</i>	Colourless
<b>Melting point/range</b>	Not applicable
<b>Boiling point/range</b>	40- 90 °c
<b>Relative density</b>	0.73
<b>PH</b>	Not applicable
<b>Solubility in water</b>	Insolubility
<b>Flash point</b>	Not applicable
<b>Viscosity</b>	Not applicable

<b>Section 10. Stability and Reactivity</b>	
<b>Conditions to be avoided</b>	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition
<b>Materials to be avoided</b>	Strong oxidizing agent

<b>Section 11. Toxicological information</b>	
<b>Inhalation</b>	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness.
<b>Ingestion</b>	Ingestion is unlikely to occur after vomiting of swallowed product aspiration into lunge is likely. Solvents may induce chemical pneumonia.
<b>Skin contact</b>	Irritating to skin (R38)

<b>Section 12. Ecological information</b>	
<b>Other adverse effects</b>	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses.

<b>Section 13. Waste Disposal</b>	
<b>Product</b>	Do not empty into drains. This material and its container must be disposed of in a safe way. Disposal should be in accordance with local, state or national legislation.

<b>Section 14. Transport</b>	
<b>UN-number</b>	1950
<b>Road/Rail - ADR/RID</b>	UN 1950 Aerosols Class: 2, PG: NA, Class code: 5F, Label: 2.1
<b>Sea-IMDG</b>	UN1950 Aerosols, Limited Quantities Class: 2, PG: NA.

<b>SICHERHEITSDATENBLATT</b>	Blatt 5/5
 	Druckdatum 03.06.2007
	Überarbeitet am 16.05.2007

<b>EmS</b>	F-D, S-U
<b>Air - IATA/CAO: Packing instr. LQ PAX CAO</b>	UN1950 Aerosols, flammable Class: 2.1, PG: NA, Label: RFG Y203 203 203

<b>Section 15. Regulatory information</b>	
<b>Warning symbol(s)</b>	F+
<b>Risk - phrase(s)</b>	R11: flammable R38: Irritating to skin.
<b>Safety-phrase(s)</b>	S2: Keep out of the reach of children. S16: Keep away from sources of ignition-No smoking. S23: Do not breathe spray. S35: This material and its container must be disposed of in a safe away. S51: Use only in well-ventilated areas.

<b>Section 16. Other Information</b>
<p>This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.</p> <p>The information contained here with is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.</p> <p>Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission form SCT Vertriebs GmbH.</p>