

Printing date 07.02.2019 Revision: 07.02.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: MANNOL 9672 Montage-Cleaner 600ml
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

SCT-Vertriebs GmbH

Feldstrasse 154

22880 WEDEL

DEUTSCHLAND

info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.



### GHS08 health hazard

Repr. 2	H361d	Suspected of damaging the unborn child

STOT RE 2 H373 May cause damage to organs through prolonged or repeated

exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



### GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



#### GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

### · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 1)

### · Hazard pictograms









GHS02 GHS07 GHS08 GHS0

### · Signal word Danger

### · Hazard-determining components of labelling:

2-methylpentane

toluene

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

# **SECTION 3: Composition/information on ingredients**

### · 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	nents:	
	1 = <b>)</b> ·   · · · · · · ·	70–80%
EINECS: 203-523-4	Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	
	/0	1 0)

(Contd. on page 3)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

	(Cor	itd. of page 2)		
	toluene	5–15%		
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336			
0.10.01	acetone	5–10%		
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336			
· Not dangerous substances				
J. 12. 12. 1	carbon dioxide	1–5%		
EINECS: 204-696-9				

• Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Do not use mouth to mouth or mouth to nose resuscitation.

Supply fresh air and to be sure call for a doctor.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness

Headache

Unconsciousness

- · Hazards Danger of pneumonia.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 3)

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## **SECTION 6: Accidental release measures**

### · 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

#### · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

### Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

#### · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

### · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Store only in the original receptacle.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in a cool place.

Store in dry conditions.

Store receptacle in a well ventilated area.

· 7.3 Specific end use(s) No further relevant information available.

3B -



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 4)

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

<ul> <li>Ingredients with limit values that require monitoring at the workplace:</li> </ul>	Ingredients with	limit values t	that require	monitoring	at the workplace:
---------------------------------------------------------------------------------------------	------------------	----------------	--------------	------------	-------------------

#### 108-88-3 toluene (15.0%)

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

Sk

### 67-64-1 acetone (10.0%)

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

### 124-38-9 carbon dioxide (5.0%)

WEL Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

· Eye protection:

(Contd. of page 5)



Tightly sealed goggles

Safety glasses

## **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

General Information

· Appearance:

Form: Liquid Colour: Clear

Odour: CharacteristicOdour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

• Flash point: Not applicable, as aerosol.

· Flammability (solid, gas): Not applicable.

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Not determined.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapour pressure: Not determined.

Density at 20 °C:
Relative density
Vapour density

0.68 g/cm³
Not determined.
Not determined.

• Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Solids content: 0.0 %

(Contd. on page 7)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
108-88-3 toluene			
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/l (mouse)	
67-64-1 ad	67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rabbit)	

- · Primary irritant effect:
- Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 8)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 7)

· Aspiration hazard

May be fatal if swallowed and enters airways.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europ	· European waste catalogue		
HP 3	Flammable		
HP 4	Irritant - skin irritation and eye damage		
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
HP 10	Toxic for reproduction		
HP 14	Ecotoxic		

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1950
- · 14.2 UN proper shipping name
- ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

(Contd. on page 9)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 8) · IMDG AEROSOLS (hexane (containing < 5 % n-hexane (203-777-6))), MARINE POLLUTANT · IATA **AEROSOLS** · 14.3 Transport hazard class(es) · ADR 2 5A Gases. · Class · Label 2.1 · IMDG 2 Gases. · Class · Label 2.1 · IATA · Class 2 Gases. · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA not regulated · 14.5 Environmental hazards: Product contains environmentally hazardous substances: 2-methylpentane Symbol (fish and tree) · Marine pollutant: Special marking (ADR): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Gases. Danger code (Kemler): · EMS Number: F-D.S-U · Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

	(Contd. of page 9)
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II	of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	3
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AERÖSOLS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

(Contd. on page 11)



Printing date 07.02.2019 Revision: 07.02.2019

Trade name: MANNOL 9672 Montage-Cleaner 600ml

(Contd. of page 10)

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

## Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 1: Aerosols – Category 1 Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.