

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: MANNOL 9906 Reifen Doctor 450ml**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture Sealant**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SCT-Vertriebs GmbH
Feldstrasse 154
22880 WEDEL
DEUTSCHLAND
info@sct-germany.de
- **Further information obtainable from:** Product safety department.
- **1.4 Emergency telephone number:** Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 2 H223-H229 Flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
Styrene-Butadiene Rubber (SBR)
- **Hazard statements**
H223-H229 Flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 1)

H317 May cause an allergic skin reaction.

- **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P280 Wear protective gloves / eye protection / face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH208 Contains Styrene-Butadiene Rubber (SBR). May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7	butane Flam. Gas 1, H220; Press. Gas C, H280	25–31%
CAS: 74-98-6 EINECS: 200-827-9	propane Flam. Gas 1, H220; Press. Gas C, H280	8–13%
EC number: 939-416-0	Styrene-Butadiene Rubber (SBR) Skin Sens. 1, H317	3–8%
CAS: 107-21-1 EINECS: 203-473-3	ethanediol STOT RE 2, H373; Acute Tox. 4, H302	3–8%
CAS: 1336-21-6 EINECS: 215-647-6	ammonia Skin Corr. 1B, H314; Aquatic Acute 1, H400	0.4–1.4%

- **Not dangerous substances**

CAS: 61790-53-2 EC number: 612-383-7	Silicium dioxide (Silicium dioxide/Kieselguhr)	0.1–0.6%
CAS: 7732-18-5 EINECS: 231-791-2	water, distilled, conductivity or of similar purity	30–38%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 2)

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO2. Do not use water.
Use fire extinguishing methods suitable to surrounding conditions.
Foam
Fire-extinguishing powder
Sand
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Particular danger of slipping on leaked/spilled product.
Wear protective clothing.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 3)

- Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane (containing $\geq 0,1\%$ butadiene (203-450-8)) (31.0%)

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

107-21-1 ethanediol (8.0%)

WEL	Short-term value: 104** mg/m ³ , 40** ppm Long-term value: 10* 52** mg/m ³ , 20** ppm Sk *particulate **vapour
-----	--

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 4)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Aerosol

Colour: White

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value at 20 °C:** 10

- **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

- **Flash point:** Not applicable, as aerosol.

- **Flammability (solid, gas):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto-ignition temperature:** Product is not selfigniting.

- **Explosive properties:** Not determined.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapour pressure:** Not determined.

- **Density at 20 °C:** 1.02 g/cm³

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not applicable.

- **Solubility in / Miscibility with**

water: Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 5)

- | | |
|--------------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 33–44 % |
| Water: | 30–38 % |
| VOC (EC) | 33–44 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide
Aldehyde
Poisonous gases/vapours
Carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

107-21-1 ethanediol

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	9,530 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 6)

- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even extremely small quantities leak into the ground.
Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**

HP 3	Flammable
HP 7	Carcinogenic
HP 11	Mutagenic
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---------------------|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 7)

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 2 5F Gases.
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1
 · **Label** 2.1

· **14.4 Packing group**

· **ADR, IATA** not regulated
 · **IMDG** III

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Segregation groups**

Ammonium compounds

· **Stowage Code**

SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0
 Not permitted as Excepted Quantity

· **Transport category**

2

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 8)

· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P3a FLAMMABLE AEROSOLS**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **National regulations:**
 - **Additional classification according to Decree on Hazardous Materials, Annex II:**
Carcinogenic hazardous material group III (dangerous).
 - **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H220 Extremely flammable gas.
 - H280 Contains gas under pressure; may explode if heated.
 - H302 Harmful if swallowed.
 - H314 Causes severe skin burns and eye damage.
 - H317 May cause an allergic skin reaction.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H400 Very toxic to aquatic life.
- **Department issuing SDS:** Product safety department.
- **Abbreviations and acronyms:**
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent

(Contd. on page 10)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2019

Version number 1906

Revision: 13.06.2019

Trade name: MANNOL 9906 Reifen Doctor 450ml

(Contd. of page 9)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 2: Aerosols – Category 2

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

· *** Data compared to the previous version altered.**

GB