

Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MANNOL 9909 Anticor schwarz 1L
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Anticorrosion additive Coating material

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND info@sct-germany.de

- · Further information obtainable from: Product safety department.
- 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit, 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- Hazard-determining components of labelling: toluene

(Contd. on page 2)



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 1)

(2E)-3-Phenyl-2-propen-1-yl beta-D-glucopyranoside

Solvent naphtha (petroleum), heavy arom.

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

· vPvB:

64742-94-5 | Solvent naphtha (petroleum), heavy arom.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|------------------------------------|---|--------|
| CAS: 108-88-3 EINECS: 203-625-9 | toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, | 15–28% |
| CAS: 1330-20-7 | H304; Skin Irrit. 2, H315; STOT SE 3, H336 xylene | 10–16% |
| EINECS: 215-535-7 | Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | |
| CAS: 85026-55-7 | (2E)-3-Phenyl-2-propen-1-yl beta-D-glucopyranoside Skin Sens. 1, H317 | 10–15% |



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

| | (Contd. of page | | |
|---|--|--------|--|
| CAS: 9003-31-0 | PI stabilized, polyisoprene, 1,3-Butadiene, 2-methyl-, homopolymer | 5–12% | |
| EC number: 618-362 | -9 Aquatic Chronic 3, H412 | | |
| CAS: 64742-94-5 | Solvent naphtha (petroleum), heavy arom. | 1–5% | |
| EINECS: 265-198-5 | vPvB | | |
| | Asp. Tox. 1, H304 | | |
| CAS: 1302-78-9 | Bentonite | 1–4% | |
| EINECS: 215-108-5 | Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | | |
| · Not dangerous substances | | | |
| CAS: 1332-58-7 | Kaolin | 10–15% | |
| CAS: 14807-96-6 | CAS: 14807-96-6 Talc (Mg3H2(SiO3)4) | | |
| EINECS: 238-877-9 | | | |
| · Additional information: For the wording of the listed hazard phrases refer to section 16. | | | |

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2. Do not use water.

Use fire extinguishing methods suitable to surrounding conditions.

Foam

Fire-extinguishing powder

Sand

- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Wear protective clothing.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene (28.0%)

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

Long-term value. 191 mg/m , 50 ppm

Sk

1330-20-7 xylene (16.0%)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk: BMGV

(Contd. on page 5)



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

1332-58-7 Kaolin (15.0%)

WEL Long-term value: 2 mg/m³

Ingredients with biological limit values:

1330-20-7 xylene (16.0%)

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift

Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Parameter: methyl hippuric acid

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 5)

| Colour: Odour threshold: Odour threshold: OH-value: Ohange in condition Melting point/freezing point: Initial boiling point and boiling range: Olecomposition temperature: Oecomposition temperature: Oecompositio | aracteristic determined. determined. |
|--|---|
| Form: Colour: Colour: Codour: Codour: Codour: Codour threshold: Co | ck aracteristic a determined. determined. determined. applicable. applicable. determined. determined. determined. applicable. determined. determined. |
| Odour: Odour threshold: Odour threshold: OH-value: Ohange in condition Melting point/freezing point: Initial boiling point and boiling range: Uncluded Individual State of the Initial boiling point of the Initial boiling point and boiling range: Idash point: Oecomposition temperature: Oecomp | determined. |
| Odour threshold: Not H-value: Not Change in condition Melting point/freezing point: Initial boiling point and boiling range: Clash point: Not Clammability (solid, gas): Not Decomposition temperature: Not Auto-ignition temperature: Explosive properties: Pro Explosion limits: Lower: Upper: Not Vapour pressure: Not | determined. determined. determined. determined. applicable. applicable. determined. determined. determined. determined. |
| Change in condition Melting point/freezing point: Initial boiling point and boiling range: Clash point: Not Clammability (solid, gas): Not Decomposition temperature: Not Explosive properties: Capposition limits: Lower: Upper: Not Mapour pressure: Not | determined. determined. determined. applicable. applicable. determined. determined. determined. determined. duct is not selfigniting. duct does not present an explosion hazard. |
| Change in condition Melting point/freezing point: Initial boiling point and boiling range: Und Clash point: Not Decomposition temperature: Not Auto-ignition temperature: Pro Explosive properties: Lower: Upper: Not Vapour pressure: Not | determined. determined. applicable. applicable. determined. determined. duct is not selfigniting. duct does not present an explosion hazard. |
| Melting point/freezing point: Initial boiling point and boiling range: Und Itash point: Not Decomposition temperature: Not Auto-ignition temperature: Pro Explosive properties: Lower: Upper: Not Vapour pressure: Not | determined. applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. |
| Initial boiling point and boiling range: Unditable Initial boiling ra | determined. applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. |
| Flash point: Flammability (solid, gas): Notecomposition temperature: Notecomposition temperature: Profixplosive properties: Explosive properties: Lower: Upper: Notecomposition temperature: Notecomposition temperature: Profixplosive properties: Notecomposition temperature: Notecomposition tempe | applicable. applicable. determined. duct is not selfigniting. duct does not present an explosion hazard. |
| Planmability (solid, gas): Note Decomposition temperature: Note Nuto-ignition temperature: Processive properties: Explosion limits: Lower: Upper: Note Note Note Note Note Note Note Note | duct does not present an explosion hazard. |
| Decomposition temperature: Not Nuto-ignition temperature: Explosive properties: Pro Explosion limits: Lower: Upper: Not Vapour pressure: Not | duct is not selfigniting. duct does not present an explosion hazard. |
| Auto-ignition temperature: Explosive properties: Explosion limits: Lower: Upper: Not Vapour pressure: Not | duct is not selfigniting. duct does not present an explosion hazard. |
| Explosive properties: Pro Explosion limits: Lower: Not Upper: Not Vapour pressure: Not | duct does not present an explosion hazard. |
| Explosion limits: Lower: Not Upper: Not /apour pressure: Not | · |
| Lower: Not Upper: Not Yapour pressure: Not | determined. |
| Lower: Not Upper: Not Yapour pressure: Not | determined. |
| /apour pressure: Not | |
| · · · | determined. |
| Density: Not | determined. |
| | determined. |
| | determined. |
| | determined. |
| Evaporation rate Not | determined. |
| Solubility in / Miscibility with | |
| | miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: Not | determined. |
| /iscosity: | |
| Dynamic: Not | |

25-44 %

25-44 %

10-15 %

No further relevant information available.

SECTION 10: Stability and reactivity

Organic solvents:

Solids content:

· 9.2 Other information

VOC (EC)

· 10.1 Reactivity No further relevant information available.



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 6)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

· LD/LC50 values relevant for classification:

· Acute toxicity Based on available data, the classification criteria are not met.

| | ATE (Acute Toxicity Estimates) | | |
|--|--------------------------------|---------------|------------------------------|
| Dermal LD50 12,500–20,000 mg/kg (rabbit) Inhalative LC50/4 h 68.8–110 mg/l | | LD50 | 12,500–20,000 mg/kg (rabbit) |
| | | 68.8–110 mg/l | |
| | 108-88-3 toluene | | |
| | Oral | LD50 | 5,000 mg/kg (rat) |
| | Dermal | LD50 | 12,124 mg/kg (rabbit) |
| | Inhalative | LC50/4 h | 5,320 mg/l (mouse) |
| | 1330-20-7 xylene | | |
| Ī | Oral | LD50 | 4,300 mg/kg (rat) |

Primary irritant effect:

Dermal

· Skin corrosion/irritation

LD50

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

2,000 mg/kg (rabbit)

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard

May be fatal if swallowed and enters airways.



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 7)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB:

64742-94-5 | Solvent naphtha (petroleum), heavy arom.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| | 1 0 0 1 |
|---------|---|
| · Europ | pean waste catalogue |
| HP4 | Irritant - skin irritation and eye damage |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP10 | Toxic for reproduction |
| HP13 | Sensitising |

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1139
- · 14.2 UN proper shipping name
- · ADR 1139 COATING SOLUTION COATING SOLUTION

(Contd. on page 9)



Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 8)

| · 14.3 | Trans | port | hazard | class | (es) | ١ |
|--------|--------------|------|--------|-------|------|---|
|--------|--------------|------|--------|-------|------|---|

· ADR, IMDG, IATA



| · Class | 3 Flammable liquids. |
|---|--|
| · Label | 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user · Danger code (Kemler): | Warning: Flammable liquids. 30 |
| · EMS Number: · Stowage Category | F-E, <u>S-E</u> E |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | of Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category · Tunnel restriction code | 3 D/E |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| UN "Model Regulation": | UN 1139 COATING SOLUTION, 3, III |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Page 10/10



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.10.2019 Version number 1910 Revision: 07.10.2019

Trade name: MANNOL 9909 Anticor schwarz 1L

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.