

Printing date 01.02.2019

Revision: 01.02.2019

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- · Application of the substance / the mixture Additive
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND info@sct-germany.de

· Further information obtainable from: Product safety department.

• 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49-551-19240

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30%) Solvent naphtha (petroleum), heavy arom.

Hazard statements

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

(Contd. on page 2)



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

(Contd. of page 1)

| (contait of page 1) | |
|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Do NOT induce vomiting. | |
| Store locked up. | |
| Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| nal information: | |
| 6 Repeated exposure may cause skin dryness or cracking. | |
| er hazards | |
| s of PBT and vPvB assessment | |
| | Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. nal information: S Repeated exposure may cause skin dryness or cracking. er hazards |

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous compone | nts' | |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|----------|
| • · | 7 Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, | ≥25–<50% |
| | aromatics (2-25%) | |
| | Asp. Tox. 1, H304; Aquatic Chronic 3, H412 | |
| EC number: 920-360- | 0 Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %) | ≥25–<50% |
| | Asp. Tox. 1, H304 | |
| | Polyolefin alkyl phenol alkyl amine | <5.0% |
| | Skin Irrit. 2, H315 | |
| | Polyether polyol | <5.0% |
| | Aquatic Chronic 3, H412 | |
| CAS: 95-63-6 | 1,2,4-trimethylbenzene | <2.5% |
| EINECS: 202-436-9 | Flam. Liq. 3, H226; Aquatic Chronic 2, H411; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | |
| CAS: 91-20-3 | naphthalene | <0.5% |
| EINECS: 202-049-5 | Carc. 2, H351; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302 | |
| · Not dangerous subs | tances | |
| CAS: 64742-94-5 | Solvent naphtha (petroleum), heavy arom. | <5.0% |
| EINECS: 265-198-5 🖌 | Asp. Tox. 1, H304 | |
| CAS: 27859-58-1 (tetrapropenyl)succinic acid | | <0.1% |
| EINECS: 248-698-8 | Eye Dam. 1, H318; Skin Irrit. 2, H315 | |
| | n. For the wording of the listed bezord phrases refer to eastion 16 | |

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

GB



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- [·] 5.1 Extinguishing media
- Suitable extinguishing agents:
- Foam

CO2, powder or water spray. Fight larger fires with water spray. Sand

- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: No special measures required.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Particular danger of slipping on leaked/spilled product. Wear protective clothing.

• 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- \cdot Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

GR



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene (2.5%)

WEL Long-term value: 125 mg/m³, 25 ppm

ILV

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection: Not required.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

| 9.1 Information on basic physical General Information | and chemical properties | |
|----------------------------------------------------------|------------------------------------|--|
| Appearance: Form: | Fluid | |
| Colour: | According to product specification | |
| Odour: | Characteristic | |
| Odour threshold: | Not determined. | |
| pH-value: | Not determined. | |
| Change in condition | | |
| Melting point/freezing point: | Undetermined. | |
| Initial boiling point and boiling | range: 160 °C | |
| Flash point: | 61 °C | |



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

| | (Contd. of page 4 |
|------------------------------------------------------|-----------------------------------------------|
| · Flammability (solid, gas): | Not applicable. |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| · Vapour pressure: | Not determined. |
| · Density: | Not determined. |
| Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic at 40 °C: | 20.5 mm²/s |
| · Solvent content: | |
| Organic solvents: | <2.5 % |
| VOC (EC) | <2.50 % |
| • 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products:
- Carbon monoxide

Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

| | | (Contd. of page 5) |
|------------|-------------|---------------------------------------------------------|
| · LD/LC50 | values rele | evant for classification: |
| ATE (Acu | te Toxicity | / Estimates) |
| Dermal | LD50 | >8–≤16 mg/kg (rat) |
| Inhalative | LC50/4 h | >24.7–46.8 mg/l |
| Hydrocar | bons, C11 | -C14, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) |
| Oral | LD50 | 15,000 mg/kg (rat) |
| Dermal | LD50 | 4 mg/kg (rat) |
| Inhalative | LC50/4 h | 13.1 mg/l (rat) |
| 95-63-6 1, | 2,4-trimet | hylbenzene |
| Oral | LD50 | 5,000 mg/kg (rat) |
| 91-20-3 na | aphthalen | 9 |
| Oral | LD50 | 490 mg/kg (rat) |
| Dermal | LD50 | 5,000 mg/kg (rat) |

· Primary irritant effect:

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eve damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

(Contd. on page 7)

GB



Printing date 01.02.2019

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

HP 5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 14 Ecotoxic

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information | | |
|------------------------------------------------------------------------------------------|-----------------------------|--|
| · 14.1 UN-Number · ADR, ADN, IMDG, IATA | not regulated | |
| 14.2 UN proper shipping name ADR, ADN, IMDG, IATA | not regulated | |
| 14.3 Transport hazard class(es) | | |
| · ADR, ADN, IMDG, IATA · Class | not regulated | |
| 14.4 Packing group ADR, IMDG, IATA | not regulated | |
| · 14.5 Environmental hazards: | Not applicable. | |
| · 14.6 Special precautions for user | Not applicable. | |
| 14.7 Transport in bulk according to Anno Marpol and the IBC Code | ex II of Not applicable. | |
| · UN "Model Regulation": | not regulated | |

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

GB -



Printing date 01.02.2019

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 01.02.2019

Trade name: MANNOL 9989 Super Benzin Oktan Plus 200ml

(Contd. of page 7) · Relevant phrases H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. · Department issuing SDS: Product safety department. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 * Data compared to the previous version altered.